Izjava o skladnosti

Proizvajalec

Flamco BV
Amersfoortseweg 9,
3750 GM Bunschoten, Nizozemska

Opis izdelka

Odzračevalnik

Tip izdelka

Flexvent
Flexvent Top
Flexvent Super
Flexvent Pro
Flexvent Max
Flexvent Top Aqua

V skladu z Direktivo o tlačni opremi 2014/68/EU, člen 4, točka 3, izjavljamo, da so zgoraj navedeni izdelki zasnovani in izdelani v skladu z dobro inženirsko prakso, da je zagotovljena njihova varna uporaba. Oznake CE na teh izdelkih ni dovoljeno namestiti.

Izdelek je bil 100-odstotno preizkušen glede tesnosti. Zahteve so izpolnjene.

Bunschoten, 19.11.2020

Podpisano za in v imenu:

FLAMCO BV

M. van de Veen

aalberts hydronic flow control

EU izjava o skladnosti

Proizvajalec	**Aalberts hfc B.V.** Fort Blauwkapel 1, 1358 DB Almere, Nizozemska
Opis izdelka	**Rešitve za zrak in nečistoče**
Tip izdelka	

Odzračevalniki:

Flexvent R⅛, R⅜, G⅜, R½, G½
Flexvent NPT NPT⅛, NPT⅜, NPT½, NPT¾
Flexvent H R½
Flexvent Top R⅜, R½
Flexvent Top Aqua R½
Flexvent Top NPT NPT⅜, NPT½
Flexvent Solar R⅜
Flexvent Top Solar G⅜
Flexvent Super G½
Flexvent Super NPT NPT¾
LTA Air Accumulator Rp½ (1,0, 1,6, 5,0 liter)

Ločevalniki zraka:

Flamco XStream Vent *22mm, G¾, G1, G1¼, G1½, G2*
Flamcovent Smart *22mm, G¾, G1, G1¼, G1½, G2*
Flamcovent Smart NPT *NPT¾, NPT1, NPT1¼, NPT1½, NPT2*
Flamcovent Smart EcoPlus *22mm G¾, G1, G1¼, G1½, G2*
Flamcovent Solar *22mm, G¾, G1*
Flamcovent Smart S DN50, DN65, DN80, DN100, DN125, DN150, DN200
Flamcovent Smart F (10 bar) DN50, DN65, DN80, DN100, DN125, DN150, DN200,
Flamcovent Smart F (16 bar) DN50, DN65, DN80, DN100, DN125, DN150, DN200

Ločevalniki nečistoč:

Flamco XStream Clean *22mm, G¾, G1, G1¼, G1½, G2*
Flamco Clean Smart *22mm, G¾, G1, G1¼, G1½, G2*
Flamco Clean Smart NPT NPT¾, *NPT1, NPT1¼, NPT1½, NPT2*
Flamco Clean Smart EcoPlus *22mm, G¾, G1, G1¼, G1½, G2*
Flamco Clean Smart S DN50, DN65, DN80, DN100, DN125, DN150, DN200
Flamco Clean Smart F (10bar) DN50, DN65, DN80, DN100, DN125, DN150, DN200
Flamco Clean Smart F (16bar) DN50, DN65, DN80, DN100, DN125, DN150, DN200
SideFlow Clean *3,5l, 5l*

Ločevalniki zraka in nečistoč:

Flamco XStream Vent-Clean *22mm, G¾, G1, G1¼, G1½, G2*
Flamcovent Clean Smart *22mm, G¾, G1, G1¼, G1½, G2*
Flamcovent Clean Smart NPT *NPT¾, NPT1, NPT1¼, NPT1½, NPT2*
Flamcovent Clean Smart EcoPlus *22mm G¾, G1, G1¼, G1½, G2*
Flamcovent Clean Smart S DN50, DN65, DN80, DN100, DN125, DN150, DN200
Flamcovent Clean Smart F (10 bar) DN50, DN65, DN80, DN100, DN125, DN150, DN200
Flamcovent Clean Smart F (16 bar) DN50, DN65, DN80, DN100, DN125, DN150, DN200

V skladu z Direktivo o tlačni opremi 2014/68/EU, člen 4, točka 3, izjavljamo, da so zgoraj navedeni izdelki zasnovani in izdelani v skladu z dobro inženirsko prakso, da je zagotovljena njihova varna uporaba. Oznake CE na teh izdelkih ni dovoljeno namestiti.

Izdelki so bili 100-odstotno preizkušeni glede tesnosti. Zahteve so izpolnjene.

Aalberts hfc B.V.
Almere, 10.04.2026